



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/618,211	07/11/2003	Jeffrey D. Provost	CISCO-7357	4216
49715 7590 12/28/2007 CISCO - THELEN REID BROWN RAYSMAN & STEINER LLP P.O. BOX 640640 SAN JOSE, CA 95164-0640			EXAMINER BROWN, MICHAEL J	
			ART UNIT 2116	PAPER NUMBER
			MAIL DATE 12/28/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

mv

Office Action Summary	Application No. 10/618,211	Applicant(s) PROVOST, JEFFREY D.	
	Examiner Michael J. Brown	Art Unit 2116	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 18 September 2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-15 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1,2,4-7,9-11,13 and 14 is/are rejected.
- 7) ☒ Claim(s) 3,8,12 and 15 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 11 July 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Allowable Subject Matter

1. Claims 3, 8, 12, and 15 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 13-14 are rejected under 35 U.S.C. 102(b) as being anticipated by Bell(US Patent 6,701,443).

As to claim 13, Bell discloses a system comprising one or more inline power devices(power supply 82, see Fig. 3), and one or more powered devices(arrangement of components 60, see Fig. 3) coupled to an inline power device, each of the one or more inline power devices and each of the one or more powered devices having at least one port(connecting medium 24, see Fig. 3), each port having a physical layer(see column 4, lines 24-25), the physical layer including an inline power control signal source(control circuitry 80, see Fig. 3) wherein an inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within

the hardware and thus the signal is originating/included on the physical layer) controls application of power to the port(see column 6, lines 26-30).

As to claim 14, Bell discloses the system wherein the inline power devices are power source equipment(power supply 82 within power apparatus 26, see Fig. 3)(see column 4, lines 21-29).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
 2. Ascertaining the differences between the prior art and the claims at issue.
 3. Resolving the level of ordinary skill in the pertinent art.
 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
-
1. Claims 1-2, 4-7, and 9-11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Bell(US Patent 6,701,443) further in view of Gephardt et al.(US Patent 5,640,573).

As to claim 1, Bell discloses a physical layer(see column 4, lines 24-25) for an inline power device(devices 22A and 22B, see Fig. 3) of a network power system(arrangement of components 60, see Fig. 3), the physical layer comprising an inline power control signal source(control circuitry 80, see Fig. 3) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus originating/included on the physical layer), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24.. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 2, Bell discloses a power source equipment(power supply 82, see Fig. 3) of a network power system(arrangement of components 60, see Fig. 3), the

power source equipment comprising at least one physical layer(see column 4, lines 24-25) including an inline power control signal source(control circuitry 80, see Fig. 3) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus originating/included on the physical layer), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 4, Bell discloses a method of inline power(power supply 82, see Fig. 3) for a network power system(arrangement of components 60, see Fig. 3), the method comprising sourcing an inline power control signal(control circuitry 80, see Fig. 3) from a

physical layer(see column 4, lines 24-25), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus the signal is originating/included on the physical layer) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 5, Bell discloses an apparatus for inline power(power supply 82, see Fig. 3) for a network power system(arrangement of components 60, see Fig. 3), the apparatus comprising a physical layer(see column 4, lines 24-25), and means for sourcing an inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) originating from the physical layer(control circuitry 80

originates from the physical layer because it is within the hardware and thus the signal is originating/included on the physical layer), wherein the inline power control signal is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 6, Bell discloses a physical layer(see column 4, lines 24-25) for an inline power device(power supply 82, see Fig. 3) of a network power system(arrangement of components 60, see Fig. 3), the physical layer comprising an inline power control signal source(control circuitry 80, see Fig. 3) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus is originating/included on the physical layer), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see

column 5, line 41) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 7, Bell discloses a power source equipment(power supply 82, see Fig. 3) of a network power system(arrangement of components 60, see Fig. 3), the power source equipment comprising at least one physical layer(see column 4, lines 24-25) including an inline power control signal source(control circuitry 80, see Fig. 3) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus is originating/included on the physical layer), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see

column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 9, Bell discloses a method of inline power(power supply 82, see Fig. 3) for a network power system(arrangement of components 60, see Fig. 3), the method comprising sourcing an inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) originating from a physical layer(see column 4, lines 24-25) (control circuitry 80 originates from the physical layer because it is within the hardware and thus the signal is originating/included on the physical layer), wherein the inline power control signal is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically

disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 10, Bell discloses an apparatus for inline power(power supply 82, see Fig. 3) for a network power system(arrangement of components 60, see Fig. 3), the apparatus comprising a physical layer(see column 4, lines 24-25), and means for sourcing an inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus the signal is originating/included on the physical layer), wherein the inline power control signal is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

As to claim 11, Bell discloses a network switch for a network power system(arrangement of components 60, see Fig. 3), the switch comprising at least one physical layer(see column 4, lines 24-25) including an inline power control signal source(control circuitry 80, see Fig. 3) originating from the physical layer(control circuitry 80 originates from the physical layer because it is within the hardware and thus is originating/included on the physical layer), wherein the inline power control signal(signal from control circuitry instructing switch 84 to close, see column 5, line 41) is configured to indicate when to apply power to a port(connecting medium 24, see Fig. 3) when there is no power applied to the port(see column 6, lines 26-30). However, Bell fails to specifically disclose the inline power control signal being configured to remove power from the port when there is power supplied to the port.

Gephardt teaches a power control signal(power control signals; see column 6, line 26) being configured to remove power from the port when there is power supplied to

the port(see column 6, lines 25-28). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Gephardt's power management unit 208 with Bells control circuitry 80 in order to have a signal which also removes power from Bell's connecting medium 24 when there is power applied to the connecting medium 24. The motivation to do so would have been to appropriately apply and remove power to a port in order to manage power of the entire system more effectively.

Response to Arguments

4. Applicant's arguments, see Appeal Brief, filed 9/18/2007, with respect to the rejection(s) of claim(s) 1-15 under 35 U.S.C. 103(a) as being unpatentable over Bell(US Patent 6,701,443) further in view of Cai et al.(US Patent 7,103,319) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of Bell(US Patent 6,701,443) further in view of Gephardt et al.(US Patent 5,640,573).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Michael J. Brown whose telephone number is (571)272-5932. The examiner can normally be reached Monday-Thursday from 7:00am-5:30pm.

Application/Control Number:
10/618,211
Art Unit: 2116

Page 13

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Rehana Perveen can be reached on (571)272-3676. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Michael J. Brown
Art Unit 2116


REHANA PERVEEN
SUPERVISORY PATENT EXAMINER
12/26/07